



76-B4442



CE

ASTM

4

( 76-B444X ) 6  
76-B446X

4

( 76-B446X )

6

4



128×80

6

CE



ASTM D1559 ASTM D5581 AASHTO T245 ASTM D6926



	<b>76-B4442</b> <b>76-B4443</b> <b>76-B4444</b>	<b>76-B4462</b> <b>76-B4463</b> <b>76-B4464</b>
	800W	2000W
( / )	55±5	55±5
	98.5mm	149.4mm
	4536±9g	10.21±0.01kg
	457±3mm	457±2mm
	385×470×1867mm	423×578×1861mm
	150kg	170kg



76-B4442



76-B4442



76-B4000/CB ASTM EN



**76-B4442**

	4	ASTM D1559, D6926	AASHO
T245		230V 50Hz 1 ph	

**76-B4443**

	4	ASTM D1559, D6926	AASHO
T245		220V 60Hz 1 ph	

**76-B4444**

	4	ASTM D1559, D6926	AASHO
T245		110V 60Hz 1 ph	

**76-B4462**

	6	4	ASTM D5581
		6	4
	230V	50Hz	1 ph

**76-B4463**

6 4 ASTM D5581  
6 4  
220V 60Hz 1 ph

**76-B4464**

6 4 ASTM D5581  
6 4  
110V 60Hz 1 ph



**33-T3712/CB**

CBR-Proctor 33-T371X 76-B444X  
B443X B446X

**76-B4460/1**

6 4 76- B446X 4